

◆フロントト一角 (単位 : 度) /Front Toe Angle (unit: degree)

		FF																		
		A									B									
		39.5	39.9	40.3	40.7	41.1	41.5	41.9	42.3	42.7	43.5	43.9	44.3	44.7	45.1	45.5	45.9	46.3	46.7	
FR	A	39.5	0	-0.3	-0.6	-0.9	-1.1	-1.4	-1.7	-2.0	-2.3	-2.9	-3.1	-3.4	-3.7	-4.0	-4.3	-4.6	-4.9	-5.1
		39.9	-	0	-0.3	-0.6	-0.9	-1.1	-1.4	-1.7	-2.0	-2.6	-2.9	-3.1	-3.4	-3.7	-4.0	-4.3	-4.6	-4.9
		40.3	-	-	0	-0.3	-0.6	-0.9	-1.1	-1.4	-1.7	-2.3	-2.6	-2.9	-3.1	-3.4	-3.7	-4.0	-4.3	-4.6
		40.7	-	-	-	0	-0.3	-0.6	-0.9	-1.1	-1.4	-2.0	-2.3	-2.6	-2.9	-3.1	-3.4	-3.7	-4.0	-4.3
		41.1	-	-	-	-	0	-0.3	-0.6	-0.9	-1.1	-1.7	-2.0	-2.3	-2.6	-2.9	-3.1	-3.4	-3.7	-4.0
		41.5	-	-	-	-	-	0	-0.3	-0.6	-0.9	-1.4	-1.7	-2.0	-2.3	-2.6	-2.9	-3.1	-3.4	-3.7
		41.9	-	-	-	-	-	-	0	-0.3	-0.6	-1.1	-1.4	-1.7	-2.0	-2.3	-2.6	-2.9	-3.1	-3.4
		42.3	-	-	-	-	-	-	-	0	-0.3	-0.9	-1.1	-1.4	-1.7	-2.0	-2.3	-2.6	-2.9	-3.1
		42.7	-	-	-	-	-	-	-	-	0	-0.6	-0.9	-1.1	-1.4	-1.7	-2.0	-2.3	-2.6	-2.9
		43.5	-	-	-	-	-	-	-	-	0	-0.3	-0.6	-0.9	-1.1	-1.4	-1.7	-2.0	-2.3	
RR	B	43.9	-	-	-	-	-	-	-	-	-	0	-0.3	-0.6	-0.9	-1.1	-1.4	-1.7	-2.0	
		44.3	-	-	-	-	-	-	-	-	-	-	0	-0.3	-0.6	-0.9	-1.1	-1.4	-1.7	
		44.7	-	-	-	-	-	-	-	-	-	-	-	0	-0.3	-0.6	-0.9	-1.1	-1.4	
		45.1	-	-	-	-	-	-	-	-	-	-	-	-	0	-0.3	-0.6	-0.9	-1.1	
		45.5	-	-	-	-	-	-	-	-	-	-	-	-	-	0	-0.3	-0.6	-0.9	
		45.9	-	-	-	-	-	-	-	-	-	-	-	-	-	-	0	-0.3	-0.6	
		46.3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	0	-0.3	
		46.7	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	0	

◆リアト一角 (単位 : 度) /Rear Toe Angle (unit: degree)

		RF																		
		D									E									
		57.2	57.6	58.0	58.4	58.8	59.2	59.6	60.0	60.4	60.8	61.2	61.6	62.0	62.4	62.8	63.2	63.6	64.0	
RR	E	57.2	0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
		57.6	0.3	0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
		58.0	0.5	0.3	0	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
		58.4	0.8	0.5	0.3	0	-	-	-	-	-	-	-	-	-	-	-	-	-	
		58.8	1.1	0.8	0.5	0.3	0	-	-	-	-	-	-	-	-	-	-	-	-	
		59.2	1.3	1.1	0.8	0.5	0.3	0	-	-	-	-	-	-	-	-	-	-	-	
		59.6	1.6	1.3	1.1	0.8	0.5	0.3	0	-	-	-	-	-	-	-	-	-	-	
		60.0	1.9	1.6	1.3	1.1	0.8	0.5	0.3	0	-	-	-	-	-	-	-	-	-	
		60.4	2.1	1.9	1.6	1.3	1.1	0.8	0.5	0.3	0	-	-	-	-	-	-	-	-	
		60.8	2.4	2.1	1.9	1.6	1.3	1.1	0.8	0.5	0.3	0	-	-	-	-	-	-	-	
RR	E	61.2	2.7	2.4	2.1	1.9	1.6	1.3	1.1	0.8	0.5	0.3	0	-	-	-	-	-	-	
		61.6	2.9	2.7	2.4	2.1	1.9	1.6	1.3	1.1	0.8	0.5	0.3	0	-	-	-	-	-	
		62.0	3.2	2.9	2.7	2.4	2.1	1.9	1.6	1.3	1.1	0.8	0.5	0.3	0	-	-	-	-	
		62.4	3.5	3.2	2.9	2.7	2.4	2.1	1.9	1.6	1.3	1.1	0.8	0.5	0.3	0	-	-	-	
		62.8	3.7	3.5	3.2	2.9	2.7	2.4	2.1	1.9	1.6	1.3	1.1	0.8	0.5	0.3	0	-	-	
		63.2	4.0	3.7	3.5	3.2	2.9	2.7	2.4	2.1	1.9	1.6	1.3	1.1	0.8	0.5	0.3	0	-	
		63.6	4.3	4.0	3.7	3.5	3.2	2.9	2.7	2.4	2.1	1.9	1.6	1.3	1.1	0.8	0.5	0.3	0	-
		64.0	4.5	4.3	4.0	3.7	3.5	3.2	2.9	2.7	2.4	2.1	1.9	1.6	1.3	1.1	0.8	0.5	0.3	0

この色の組み合わせはトレッド、ホイルベース数値が基準値よりの増減が多い為、推奨外となります。